

DS-2CE12DF3T-PIRXOS

2 MP ColorVu PIR Siren Audio Fixed Bullet Camera

ColorVu




- High quality imaging with 2 MP, 1920 × 1080 resolution
- 24/7 color imaging with F1.0 aperture
- Clear imaging against strong back light due to 130 dB true WDR technology
- 3D DNR technology delivers clean and sharp images
- 2.8 mm, 3.6 mm, 6 mm fixed focal lens
- Up to 40 m white light distance for bright night imaging
- Detects human body through heat-sensitive passive infrared (PIR)
- Active strobe light and audio alarm to warn intruders off
- High quality audio with audio over coaxial cable, built-in mic, and built-in speaker
- Water and dust resistant (IP67)



▪ Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Frame Rate	TVI: 1080p @ 25 fps/30 fps
Min. Illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm, 3.6 mm, 6 mm fixed focal lens
Field of View	2.8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116° 3.6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91° 6 mm, horizontal FOV: 51°, vertical FOV: 28°, diagonal FOV: 59°
Lens Mount	M12
Light Alarm	Flashing Light Alarm (Red & Blue)
Day & Night	Color
WDR (Wide Dynamic Range)	≥130 dB
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Menu	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT/HIGHLIGHT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR, BLC, HLC, Global, HLS
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable motion areas
Noise Reduction	3D DNR/2D DNR
Language	English
Function	Brightness, Contrast, Mirror, Defective Pixel Correction, Sharpness, Anti-Banding, Smart Light
Interface	
Video Output	1 HD analog output
Alarm	1 line out
Audio In	Built-in mic
General	
Operating Conditions	-40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC ± 25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
Consumption	Max. 11.4 W
Protection Level	IP67
Material	Front cover: Metal, Main body: Plastic
White Light Range	Up to 40 m
PIR Range	Angle: 110°, Range: 11 m
Communication	HIKVISION-C
Dimension	82.6 mm × 77.1 mm × 213.2 mm (3.25" × 3.04" × 8.39")
Weight	Approx. 467 g (1.03 lb.)

▪ Dimension




▪ Accessory

▪ Optional

DS-1280ZJ-XS

Junction box



▪ Available Model

DS-2CE12DF3T-PIRXOS

Distributed by:



HIKVISION™

Headquarters

No.355 Qianmo Road, Qianjiang District,
Hangzhou 310051, China
T +86-571-8607-8888
www.hikvision.com

Hikvision USA
T +1-800-855-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8588-4235
sales.au@hikvision.com

Hikvision India
T +91-22-28450000
sales@promethikvision.com

Hikvision Canada
T +1-866-200-5680
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-8888
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6802
info.it@hikvision.com

Hikvision Brazil
T +55-11-3318-0050
ltsm.support@hikvision.com

Hikvision Turkey
T +90-215571 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652 2433
sales.my@hikvision.com

Hikvision UK & Ireland
T +4428-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (0) 3351172
sales.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-5730667
nikita.pantukh@hikvision.ru

Hikvision Vietnam
T +84-974270388
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4422680
sales.me@hikvision.com

Hikvision Singapore
T +65-6894-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-15-55
info.es@hikvision.com

Hikvision Tashkent
T +99-67-1228-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2751-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-668-67-98
sales.ru@hikvision.com

Hikvision Korea
T +82-(0)31-721-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-450-81-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com